

TURBO LEVO FSR EXPERT CE TLD 6FATTIE



TLD

Lorsque nous avons lancé les travaux de développement du Turbo Levo FSR Expert 6Fattie, nous avons commencé par créer un VTT offrant toutes les caractéristiques qui font la réputation des vélos Specialized, avec un design adapté de manière à permettre la parfaite intégration de notre technologie Turbo.

- Le cadre utilise notre aluminium M5 Premium pour son équilibre idéal entre résistance, légèreté et réactivité. Sa géométrie Trail inclut toutes les caractéristiques des VTT Specialized, comme le boîtier de pédalier bas, le tube horizontal long et les bases ultra courtes. Les systèmes de câbleries sont totalement intégrés, y compris celui de la tige de selle télescopique Command Post IRcc, tandis que le moteur et la batterie sont entièrement intégrés dans le tube diagonal.
- La fourche RockShox Pike RC est équipée d'un axe traversant Maxle Ultimate de 15 x 110 mm et un ressort Solo Air™. Avec son débattement de 140 mm, elle amortit confortablement les petits comme les gros chocs avec une efficacité maximale.
- Les freins SRAM Guide RS sont les plus puissants et modulables de la catégorie. Leur étrier à quatre pistons et la toute dernière évolution du système de came SwingLink™ assurent des freinages constants et modulables pour un poids raisonnable et une dissipation optimale de la chaleur.

PART NO.	DESCRIPTION	COLOR	SIZE
95217-3702	LEVO FSR EXPERT CE 6FATTIE	TLD	S
95217-3703			M
95217-3704			L
95217-3705			XL

LEVO FSR					
SIZE	S	M	L	XL	
Seat Tube Length, Center to Top (mm)	396	435	468	520	
Top Tube Length, Horizontal (mm)	555	585	615	650	
Bottom Bracket Drop (mm)	21	21	21	21	
Bottom Bracket Height (mm)	342	342	342	342	
Chainstay Length (mm)	459	459	459	459	
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3	69.3	
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9	73.6	
Head Tube Angle (deg)	66.5	66.5	66.5	66.5	
Wheel Base (mm)	1154	1181	1212	1246	
Standover Height (mm)	755	763	773	781	
Head Tube Length (mm)	95	100	130	150	
Stack (mm)	596	600	628	646	
Reach (mm)	389	415	434	460	
Handlebar Width (mm)	750	750	750	750	
Stem Length (mm)	45	60	60	60	
Saddle Width (mm)	143	143	143	143	
Seat Post Length (mm)	390	430	430	430	
Crank Length (mm)	165	170	170	170	



SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 140mm of travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 197x47.6mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 140mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM X01, carbon cage, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM XG-1180, 11-speed, 10-42t
CHAIN	SRAM PCX1, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
PA MOTOR	Exclusive custom tune and software, Trail Tune, 250W
PA USER INTERFACE/REMOTE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
PA BATTERY	Custom LEVO battery, 504Wh, 40x3.5Ah, ANT+/Bluetooth connectivity, IP 67
PA CHARGER	Custom charger, 42V4A w/Rosenberger plug
PA WIRING HARNESS	Custom harness w/ Rosenberger plug